

**CERTIFICATE OF COMPLIANCE  
OF PRODUCTION CONTROL ON-SITE**

**CE N° 0380 - CPR - 602**

In the framework of the EU Regulation N° 305/2011 set forth by the European Parliament and the Council on 09 March, 2011, which harmonised the conditions to commercialise construction products and repealed Directive 89/106/CEE of the Council, it was established that for the following product:

**MDF FR M2**

**Thickness : 4 mm / Density : 870 kg/m<sup>3</sup> (+/- 5%)**

**Classification: C-s2,d0 according to EN 13501-1**

(European classification report n° FCBA 15/RC-62),

(Terms of use of the product: see attached annex)

**Produced by: ISOROY PANNEAUX DE CORREZE SAS**

**Manufactured in the facility located in:**

**6 impasse de l'Empereur - CS 70126 - 19204 USSEL**

FCBA, as the notified body N° 0380, determined the typical product on the basis of typical tests (including sampling), calculations concerning the type, values from tables or documentation describing the product; carried out the initial inspection of the fabrication facility and tested production on site, as well as carrying out surveillance, assessment and continuous approval of the on-site production (system 1).

The present certificate attests that all provisions concerning the conformity attestation of the on-site production set forth in the harmonised technical specification of reference **NF EN 13986: 2004 + A1 : 2015** have been applied.

This certificate was issued for the first time on **29/03/2016**, and except for withdrawal or suspension, shall remain valid as long as the conditions described in the harmonised technical specifications, production conditions on the site and production testing in the facility shall continue to conform.

The list of valid certificates of conformity can be accessed on the [www.fcba.fr](http://www.fcba.fr) site.

*(In case of litigation, only the French version of the present certificate is the authentic text).*

## **ANNEX**

**CE Performance constancy Certificate**  
**N° 602/2016-GB/2 du 27/04/2017**

**CLASSIFICATION IS VALID IN TERMS OF USE FOLLOWING PRODUCT**

**« MDF FR M2 »:**

**This classification is valid for the following end use applications:  
mechanical fixation on A2-s1,d0 or better substrate-with a minimal density of  
525 Kg/m<sup>3</sup> and minimal thickness of 12m.**